

# Remote Control Switch

230V~ Mains Powered

## Model Ei1529RC

- For use with 2100, 160RC and 140RC Series smoke and heat alarms and 260RC Series Carbon Monoxide (CO) alarms
- Three functions:
  - Test: to test alarms
  - Locate: to identify triggered alarm
  - Hush: to silence alarms
- Mains Check feature
- 5 year guarantee



## Product Description

The Ei1529RC is a Remote Control Switch that runs on 230V AC mains power. It is designed for use with 2100, 160RC and 140RC Series smoke and heat alarms, and 260RC series Carbon Monoxide alarms.

It increases the flexibility and user friendliness of the alarms by allowing the user to remotely 'Locate', 'Hush' and 'Test' the alarms in the system:

- **Locate** the source of the alarm
- **Hush** any nuisance alarms
- **Test** the alarm system
- **Mains Check** provides warning of a mains failure

## Operation

- If the alarm system is triggered, the system can be remotely controlled via the switch:
- **'Locate' Switch**  
Audibly identifies the alarm that has triggered by silencing all other alarms for approximately 10 minutes. Automatically resets after this period.
- **'Hush' Switch**  
Silences any nuisance alarms for approximately 10 minutes. Automatically resets after this period.
- **'Test' Switch**  
Causes all alarms in the system to sound. It is equivalent to pressing the test button on each alarm.
- **Mains Check**  
Provides warning of a mains failure, as the Test feature will not operate in the absence of mains power.



Mile End Business Park, Oswestry, Shropshire SY10 8NN

Tel. 01691 664100

Fax. 01691 664111

www.aico.co.uk

E & OE Cur policy is one of continuous improvement.

We reserve the right to amend designs and specifications without prior notice.

Ei1529RC DataSht Rev 2 06.12.13

## Model Ei1529RC

### Technical Specification

1. Complies with electrical safety requirements: BS 415: 1990
2. Carries the CE mark to indicate conformance to Low Voltage and Electromagnetic Compatibility Directives.
3. Wall mounted for ease of use - can be fixed with surface mount box supplied, or will fit a standard recessed box (not supplied)
4. Suitable for siting at any convenient point in the property. Up to 4 x Ei1529RC switches can be installed in a system along with a maximum of 20 x 2110, 160RC or 140RC Series smoke and heat alarms or 260ENRC Series Carbon Monoxide alarms..
5. The unit incorporates 3 switches marked Locate, Test and Hush. These provide control features as detailed in points 6, 7 and 8 below and a mains check function as per point 9 below.
6. **Locate:** When the system is in an alarm state, pressing and releasing the Locate switch will silence all alarms in the system except for the alarm that initiated the alarm state. This feature allows easy identification of either the source of a nuisance alarm, or the site of a real fire.  
Note: Pressing the Locate switch temporarily disables the interconnect line between the alarms, it does not disable the individual alarms in the system. Each alarm is still fully functional as a stand-alone unit until the system automatically resets within 10 minutes of operation. The system can be manually reset at any time by pressing the Test switch until all the alarms sound.
7. **Test:** Pressing the Test switch into the 'on' position will test all the alarms in the system. This operation is equivalent to pressing the test button on all alarms in the system simultaneously and as such performs a true functional test of the system without having to reach up to each alarm in turn. Pressing the Test switch overrides the Locate function and resets the system to standby.
8. **Hush:** Momentarily pressing the Hush switch allows remote silencing of false alarms. The system will reset automatically after approx 10 minutes. In the unlikely event that a fire should occur during the 'Hush' period the feature will be overridden when sufficient smoke has entered the sensor chamber of the Smoke Alarms in the system, or sufficient CO has entered the sensor of the CO alarms in the system. Note: the Hush feature will not operate if the CO alarm is sensing CO levels of 300ppm or above due to the increased danger.
9. **Mains Check:** Provides warning of mains failure, as the Test feature will not operate in the absence of mains power.
10. Easily installed via a 3 wire connection of Live, Neutral and Interconnect/Control (as standard Smoke/Heat Alarm wiring).
11. Dimensions: 90mm x 90mm x 40mm deep.
12. Weight inclusive of packaging: 240g.
13. Manufactured in Ireland.



Mile End Business Park, Oswestry, Shropshire SY10 8NN Tel. 01691 664100  
E & OE Our policy is one of continuous improvement.  
We reserve the right to amend designs and specifications without prior notice.

Fax. 01691 664111 www.aico.co.uk  
Ei1529RC DataSht Rev 2 06.12.13

Aico Ltd is a wholly owned subsidiary of Ei Electronics



Europe's Leader in Residential Fire + Gas Detection  
Ei Electronics, Shannon, Ireland



Made in  
Ireland